



技术参数:

插芯:

- 插针数: 6
- 额定电流: 16A
- 额定电压: 830V
- 额定脉冲电压: 8kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V
- 绝缘阻抗: $>10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: >500

插针:

- 接线方式: 冷压连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻: $<1\text{m}\Omega$
- 线径范围: $0.14-4\text{mm}^2(26-12\text{ AWG})$

工具:

- 冷压钳:
 - TL02G($0.5-4\text{mm}^2$)
 - TL02($0.14-0.37\text{mm}^2$)
- 退针器: TL01

Technical specification:

Insters:

- No. of contact: 6
- Rated current: 16A
- Rated voltage: 830V
- Rated impulse voltage: 8kV
- Pollution degree: 3
- Rated voltage acc.to UL: 600V
- Insulation resistance: $>10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: >500

Contacts:

- Terminal: crimp terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance: $<1\text{m}\Omega$
- Wire gauge: $0.14-4\text{mm}^2(26-12\text{ AWG})$

Tools:

- Crimp contact tool:
 - TL02G($0.5-4\text{mm}^2$)
 - TL02($0.14-0.37\text{mm}^2$)
- Contact removal tool: TL01

						表面处理 Finish		-		图号 Drawing No.		-		
						材料 Material		-		产品代号 Part Code		HVME-006-FC		
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date	比例 Scale		版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.		2112064201	
绘图 Drawn		姓名/Name	日期/Date	姓名/Name	日期/Date	1:1	V1.0	9.8g	-		产品名称 Part Name		-	
审核 Checked			18.10.2010											
工艺 Process				批准 Approved	18.10.2010						All Dimensions in mm Original Size DIN A 4		浙江西霸士电气有限公司	