



技术参数:

插芯:

- 插针数: 2
- 额定电流: 70A
- 额定电压: 1000V
- 额定脉冲电压: 8kV
- 污染等级: 3
- 依据UL的额定电压: 600V
- 绝缘阻抗:  $> 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数:  $> 500$

插针:

- 接线方式: 轴向螺栓连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻:  $< 0.5\text{m}\Omega$
- 线径范围: 14-22mm<sup>2</sup>
- 内六角扳手: HEXA-D2
- 剥线长度:
  - mm<sup>2</sup>: 6 10 16 22
  - mm: 11<sup>+1</sup> 11<sup>+1</sup> 11<sup>+1</sup> 12.5<sup>+1</sup>
- 拧紧力矩:
  - mm<sup>2</sup>: 6 10 16 22
  - N·m: 2 3 4 5

Technical specification:

Insters:

- No. of contact: 2
- Rated current: 70A
- Rated voltage: 1000V
- Rated impulse voltage: 8kV
- Pollution degree: 3
- Rated voltage acc.to UL: 600V
- Insulation resistance:  $> 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles:  $> 500$

Contacts:

- Terminal: axial screw terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance:  $< 0.5\text{m}\Omega$
- Wire gauge: 14-22mm<sup>2</sup>
- Hexagonal driver: HEXA-D2
- Stripping length:
  - mm<sup>2</sup>: 6 10 16 22
  - mm: 11<sup>+1</sup> 11<sup>+1</sup> 11<sup>+1</sup> 12.5<sup>+1</sup>
- Tightening torque:
  - mm<sup>2</sup>: 6 10 16 22
  - N·m: 2 3 4 5

						表面处理 Finish		-		图号 Drawing No.	-	
						材料 Material		-		产品代号 Part Code	HMK70-002.2-M	
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date	比例 Scale		版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.	2112122101
绘图 Drawn		姓名/Name	日期/Date	姓名/Name	日期/Date	4:3	V1.0	31g	-		产品名称 Part Name	-
审核 Checked			18.10.2010									
工艺 Process				批准 Approved								
								All Dimensions in mm Original Size DIN A 4		浙江西霸士电气有限公司		